

Technical Datasheet - Compact Version

Key Features

- Real-time control for up to 250,000 parameters per session with grandMA3 processing units
- 6 DMX outputs, 1 DMX input
- 2 internal foldable multi-touch monitor screens
- 2 internal letterbox multi-touch screens
- 2 internal multi-touch command screens
- Supports 2 external multi-touch screens
- 41 RGB backlit rotary encoders
- 5 dual backlit encoders
- 15 backlit motorized 60 mm faders
- 60 separate playbacks
- 16 assignable x-keys
- Integrated keyboard drawer
- Built-in uninterruptible power supply (UPS)
- 3 etherCON connectors, 6 USB connectors
- 2 backlit motorized A/B faders (100 mm)
- Individually backlit and dimmable silent keys (clickless)

Technical Specifications

Parameters	16,384 (HTP/LTP)
Parameters Mode 2	4,096 (HTP/LTP)
Operating Voltage / Supply Voltage	AC 100 - 240 V; 50/60 Hz
Power	max. 300 VA
Operating Temperature	0 °C to 40 °C / 32 °F to 104 °F

Dimensions

Folded (drawer closed)	854 x 539 x 181 mm / 34 x 22 x 8 in
Operational (unfolded)	854 x 584 x 409 (max. 450) mm / 34 x 23 x 17 (max. 18) in
Fully Unfolded + Drawer opened	854 x 871 x 255 mm / 34 x 35 x 10 in

Net Weight: 33 kg / 73 lbs

Connectors

Power	1 x powerCON TRUE1
Network	3 x etherCON/RJ45
DMX512-A Out	6 x (5-pin XLR female)
DMX512-A In	1 x (5-pin XLR male)

MIDI In	1 x (5-pin DIN female)
MIDI Out	1 x (5-pin DIN female)
Linear Timecode	1 x (3-pin XLR female)
Audio In	1 x (3-pin XLR female)
GPI Remote Control	1 x D-SUB DE9 female
External Screens	2 x DisplayPort 1.2
S/PDIF	2 x (In/Out)
USB 2.0	3 x (Type A)
USB 3.0	3 x (Type A)
LED Desk Light	2 x (4-pin XLR female)