


MODEL: ACTORIS FRESNEL

CODE: AL2700

October 7, 2025



LIGHT SOURCE:

- Source type:**
 - LED (Red + Green + Blue + Amber + Lime + Royal Blue)
 - Power:**
 - 370 W
 - Color temperature:**
 - 2500 to 10.000 K – with perfect Plank-curve CCT
 - CRI:**
 - Up to 95
 - LED life expectancy:**
 - 50.000 L70*
- * *It may vary depending on various factors, such as the type of use and environment*

PHOTOMETRIC DATA:

- Zoom range:**
 - 16° – 80°
- Lm output:**
 - Up to 12.750 Lm (integrating sphere)
- Front lens:**
 - Ø 200 mm

NOISE LEVEL:

- Autofan mod.:**
 - Variable output
 - Fixed presets:**
 - Auto: 34.9 dB
 - 35 dB: 35.0 dB
 - 30 dB: 30.0 dB
 - 27 dB: 26.7 dB
 - 25 dB: 24.7 dB
 - Fanless*: 23.9 dB
- * With reduced output

CONTROL & CONNECTIONS:

- Personalities:**
 - 4 modes + 1 stand alone
 - 33 / 17 / 9 / 1 DMX control parameters
- Protocols:**
 - DMX, Art-Net, sACN, RDM
- Connectors:**
 - Locking 5 pin XLR IN/OUT
 - RJ45 IN/OUT
- Power con.:**
 - PowerCon True1 IN/OUT
- Web server:**
 - Built-in
- CloudIO:**
 - Fully compatible
 - On-field calibration for color consistency

DYNAMIC EFFECTS:

- Colors:**
 - Colors control mode RGBAL + ROYAL BLUE
 - Tungsten mode, to replicate the behavior of a tungsten lamp during dimming from 0 to 100% and vice versa
 - Tint correction: ± green/magenta adjustments
 - Flicker-free, thanks to PWM frequency adjustment
 - Color control with Advanced, Standard, White and Single-Channel modes
 - Color temperature adjustment
 - Wide color gamut and extended spectrum, including deep blue and deep red
 - Combined fixture calibration ensures colors consistency despite changes in temperature and over time
 - Wavelength binning selection and 100% fixture calibration ensures color repeatability fixture-to-fixture

- Dimmer:**
- High resolution electronic dimmer - 24 bit, 5 curves

HARDWARE & SOFTWARE:

- Long life self-charging battery
- Display graphic LCD backlit B/W display
- Firmware upload from another fixture
- Firmware upgrade via Web Server
- Diagnostic
- DMX monitoring
- Remote access through RDM

HOUSING:

- Aluminum and steel structure with plastic covers
- One handle for transportation
- IP20 rated
- Built in bracket
- Optional safety chain
- Working in any position

ELECTRICAL:

- Operating voltage:**
- 100-240V, 50/60Hz
- Power Supply:**
- Electronic auto range with active PFC
- MAX Power consumption:**
- Max 570W (5,7A) @ 100V

THERMAL SPECIFICATION:

- MAX Ambient temperature:**
- 45°C (113°F)
- Min Ambient Temperature:**
- -20°C (-4°F)
- MAX temp. of the ext. surface:**
- 90°C (194 °F)
- Total heat dissipation:**
- 1400 BTU/hr ±10% / 1476 kJ/hr ±10%

SAFETY SPECIFICATIONS:

- Min. dist. of illum. objs:**
- 0,2 m (8")
- Min. dist. from flamm. mat.:**
- 0,2 m (8")
- Protections:**
- Forced ventilation with axial fans
 - T6.3A fuse 250V – 5x20 mm (External main fuse)
 - T6.3A fuse 250V – 5x20 mm (External fuse)

COMPLIANCE:

CE Marking (in conformity to the following):

- 2014/35/EU – Low Voltage directive (LVD)
- 2014/30/EU – Electromagnetic compatibility of equipment (EMC)
- 2011/65/EU - Restriction of the use of certain hazardous substances (RoHS)
- 2009/125/EC - EcoDesign requirements for Energy-related Products (ErP)

UKCA conforms to UK regulations:

- S.I. 2016 N.1101
- S.I. 2016 N.1091
- S.I. 2012 N.3032
- S.I. 2021 N.745

cMETus LISTED:

- UL1573
- CSA C22.2 N.166:2015

PACKAGING:

- Carton box + Polystyrene
- Carton box
- Flight case

WEIGHT & SIZES:

- Weight:**
- 11 Kg
 - 24,25 lbs
- Dimensions:**
- 342 x 560 x 341 mm
 - 13,4 x 22,0 x 13,4 in

ACCESSORIES:

- ETL Power:**
- CAB02B/802 (Included)
 - * Cord 1.5 m (bare end with IP65 PowerConTrue1 conn.)
- Pole bracket:**
- AA2050000102 (Optional)
- Barndoor:**
- AA2051000102 (Optional)
- Soft box:**
- AA2053000102 (Optional)
- Snoot:**
- AA2054000102 (Optional)
- Foam shell:**
- AL2700C41100F (Optional)
- Clamp:**
- C21070 (Optional)
- Safety Chain:**
- 105041/001 (Optional)