

Technical Datasheet - Mini Version

Key Features

- Real-time control for up to 250,000 parameters per session with grandMA3 processing units
- 6 DMX outputs, 1 DMX input
- 1 internal foldable multi-touch monitor screen
- 1 external multi-touch screen can be connected
- 29 RGB backlit rotary encoders
- 5 dual encoders
- 10 backlit motorized 60 mm faders
- 40 separate playbacks
- 16 assignable x-keys
- 3 etherCON connectors, 5 USB connectors
- 2 backlit motorized A/B faders (100 mm)
- Individually backlit and dimmable silent keys (clickless)

Technical Specifications

Parameters	8,192 (HTP/LTP)
Parameters Mode 2	4,096 (HTP/LTP)
Operating Voltage / Supply Voltage	AC 100 - 240 V; 50/60 Hz
Power	max. 250 VA
Operating Temperature	0 °C to 40 °C / 32 °F to 104 °F

Dimensions

Folded	661 x 429 x 160 mm / 26 x 17 x 7 in
Unfolded	661 x 563 x 325 (max. 410) mm / 26 x 23 x 13 (max. 17) in

Net Weight: 16 kg / 36 lbs

Connectors

Power	1 x powerCON TRUE1
Network	3 x etherCON/RJ45
DMX512-A Out	6 x (5-pin XLR female)
DMX512-A In	1 x (5-pin XLR male)
MIDI In	1 x (5-pin DIN female)
MIDI Out	1 x (5-pin DIN female)
Linear Timecode	1 x (3-pin XLR female)
Audio In	1 x (3-pin XLR female)

GPI Remote Control	1 x D-SUB DE9 female
External Screens	1 x DisplayPort 1.2
S/PDIF	2 x (In/Out)
USB 2.0	3 x (Type A)
USB 3.0	2 x (Type A)
LED Desk Light	1 x (4-pin XLR female)